



**PERFORMANCE
SEALING
SOLUTIONS**

Distributed by:

PTFE Thread Sealant Tape *White Grades*



Outstanding Quality – Outstanding Performance!!

Made in USA

Forms Tight, Reliable Seal

Made of 100% virgin PTFE

MIL-SPEC & FDA Compliant

Our **PTFE Thread Sealant Tape** is the ideal solution for superior sealing of pipe threads up to 2" diameter. Available in 3 density grades, our tape can be used in a wide variety of applications including:

- ▶ *General purpose water, air, steam & hydraulic service*
- ▶ *Demanding service such as solvents, fuels & alkalis*
- ▶ *Critical applications such as oxygen, hydrogen & acids*
- ▶ *All types of piping components & equipment such as valves, filters, tanks, pressure vessels, pumps & compressors*
- ▶ *and many other applications*

PTFE Thread Sealant Tape

Description

TFCO **PTFE Thread Sealant Tape** is the ideal solution for sealing threaded pipe connections up to 2" diameter. Our thread sealant tape provides a tight seal while providing natural lubrication to prevent damaging the threads. Made of 100% PTFE, it is resistant to most common chemicals, and is rated for temperatures from -450 deg F to +550 deg F. Available in 5 different widths and 3 densities, our tapes can be used in a wide variety of applications, from general purpose service such as water and air, to difficult service such as acids and pure oxygen.



Available Sizes / Quantities

Size	Case Quantity	
	Standard Case (White Box)	Display Case
1/4" x 260"	144	125
1/4" x 520"	144	125
1/2" x 260"	144	125
1/2" x 520"	144	125
1/2" x 1296"	144	80
3/4" x 260"	144	75
3/4" x 520"	144	75
3/4" x 1296"	144	48
1" x 260"	144	75
1" x 520"	144	75
1" x 1296"	144	48
2" x 520"	72	-
2" x 1296"	72	-

Display Box

- Perfect for Counters or Shelves
- 12" Wide x 12" Deep
- 4.5" H closed; 10.5" H open, to top of back panel

Specifications (White Grades)

	Standard Grade	High Grade	Premium Grade
Widths	1/2" • 3/4" • 1" • 2"	1/4" • 1/2" • 3/4" • 1" • 2"	1/4" • 1/2" • 3/4" • 1" • 2"
Application	General Purpose	Demanding	Critical
Thickness	3.0 – 3.5 mil	3.0 – 3.5 mil	3.0 – 3.5 mil
Density	0.5 – 0.7 g/cc	0.9 – 1.2 g/cc	1.2 – 1.4 g/cc
Pressure Rating	2,000 psi	10,000 psi	10,000 psi
Temperature Rating	-450°F to 550°F	-450°F to 550°F	-450°F to 550°F
pH Range	0 – 14	0 – 14	0 – 14
Specifications	MIL-SPEC T27730A FDA 21 CFR 177.1550	MIL-SPEC T27730A FDA 21 CFR 177.1550	MIL-SPEC T27730A FDA 21 CFR 177.1550 A-A-58092